


BJ153

内槽压板



本体
S45C
淬火回火
四氧化三铁膜

型号	L	W	H	W ₁	L ₂	M	L ₁	L ₃	夹紧力(kN) 突出量 max.~min.	容许紧固扭矩 (N·m)	质量 (g)					
BJ153-08040	40	19	12	9	6	M 8×1.25	10	32	5.3~7.3	17	50					
BJ153-08050	50				14		12	4~7.6	60							
BJ153-08063	63				27		55	3.1~8.3	70							
BJ153-10050	50	25	12	11	8	M10×1.5	12	40	8.5~11.9	34	80					
BJ153-10063	63				18		53	6.4~12.2	100							
BJ153-10080	80				32		70	7.4~17.7	170							
BJ153-10100	100	16	16	11	40	M10×1.5	15	90	8.8~18.8	45	220					
BJ153-10125	125				50		115	9.8~19.6	280							
BJ153-12063	63				14		14	13	M12×1.75		20	52	13.7~21.6	71	190	
BJ153-12080	80	25	69	10.3~21	240											
BJ153-12100	100	40	89	10.9~25.8	350											
BJ153-12125	125	19	19	13	50	M12×1.75	20	114	12.9~27.5	80	440					
BJ153-12160	160				60			149	15.4~28.8		570					
BJ153-16080	80				19			17	17		M16×2	25	18	65	16.6~26	115
BJ153-16100	100	85	14.2~28.4	540												
BJ153-16125	125	110	14.7~31.1	670												
BJ153-16160	160	25	25	17	65	M16×2	25	145	15.3~33.4	129	850					
BJ153-20160	160				50			21	60		M20×2.5	32	144	16.5~35.6	183	1140
BJ153-20200	200												80	184		17.9~37.8

使用示例及使用方法

