

# CP735



## 快速柔性定位器(套子)



(圆锥套)



(直柱套)




类型	本体	圆锥套
CP735-L	SCM440 四氧化三铁膜	SCM440 盐浴软氮化处理
CP735-S	淬火回火	-

型 号	类型	D (g6)	H	d	H <sub>1</sub>	D <sub>p</sub>	M	顶起力 (N)注)	质量 (g)
CP735-0939L	圆锥套	38	15	4.5	10	30	M5×0.8	300	100
CP735-0939S	直柱套							-	101
CP735-1246L	圆锥套	45	19	4.5	14	37	M6×1	450	179
CP735-1246S	直柱套							-	184
CP735-1656L	圆锥套	55	24	5.5	18	45	M6×1	680	337
CP735-1656S	直柱套							-	341


注) 顶起力指的是本体内置弹簧顶起可动式圆锥套的力量。(参照 P.84)

### 使用示例及使用方法

#### ■ 安装孔加工尺寸



#### ■ 加工精度



规 格	d <sub>1</sub> (H7)	H <sub>2</sub> (±0.05)	d <sub>2</sub>	H <sub>3</sub>	M
CP735-0939	38	15.5	13	23	M4×0.7
CP735-1246	45	19.5	16	28	
CP735-1656	55	24.5	20	34	M5×0.8

### 相关产品页

- CP730 快速柔性定位器六角螺栓型(销子)(参照 P.78)
- CP731 快速柔性定位器凸轮型(销子)(参照 P.79)
- CP735-P 快速柔性定位器(防护套)(参照 P.81)

### 参照页

快速柔性定位器六角螺栓型和凸轮型特点及使用方法 (参照 P.84)